

# Performance Beast

Durable Strength & Conditioning Surfacing

BUILT ON  
**itsTRU**<sup>®</sup>  
TECHNOLOGY

## PRODUCT ATTRIBUTES

- **2.5mm Vulcanized Composition Rubber (VCR) Surface Layer**  
Provides excellent durability and slip resistance
- **8mm Factory Fusion-Bonded VCR Beast Base Layer**  
Extremely dense, upcycled VCR minimizes bar bounce and provides ultimate durability

Made using our patented itsTRU<sup>®</sup> technology, Performance Beast is a durable 10.5mm vulcanized composition rubber system that absorbs shock. Designed for heavy strength training, Performance Beast maximizes energy restitution and enhances durability in applications dominated by free weight training



## APPLICATIONS

- Selectorized Strength
- Free Weights
- Olympic Style Lifting
- Functional Training
- Cardio

## BENEFITS

- Extreme durability
- Sustainable
- Slip-resistant
- Provides substrate protection

## NOMINAL DIMENSIONS

Available as a standard in rolls. Talk to your local sales rep to determine availability, pricing, minimums, and lead times.



10.5mm [2.5mm + 8mm] x 48" [1.22m]

NRG<sup>™</sup>



**Force Reduction: 11.4%**  
Absorption of impact energy




**Energy Restitution: 72.2%**  
Useful return of impact energy

*Typical Deltec Field Tester Results*



# Performance Beast


## COLOR SWATCHES




Medium Gray ES504




Charcoal ES505




Dark Taupe ES506




Warm Gray ES507




Navy ES508



Green ES509




Maroon ES510



Red ES511




Steel Appeal 2 ES15A




Dark Gray ES502




Mocha Latte 2 ES43A




Blue ES500




Blue Jays ES103




Cardinals ES104




Raiders ES503




Buff Blue 20 ES45




Rippin Red 20 ES47



Grippin Gray 20 ES46



Whey Protein 2 ES97A



Basic Black ES00

## TECHNICAL DETAILS

Performance Criteria	Test Standard	Typical Results
Recovery after Static Load	ASTM F970	0.004"
Coefficient of Friction	ASTM D2047	>0.8
FloorScore	CA 01350	Certified
Abrasion Resistance	ASTM D3389	Pass
Flammability - Pill Test	ASTM D2859	Pass
Impact Insulation Class (IIC)*	ASTM E492	55
Delta IIC*	ASTM E2179	24

\*Tested on a 6" concrete slab with no ceiling.